

Summary of Greenfield Housing Code Development Standards (Parallel Road Lot)

This document includes a summary of the development standards of Greenfield Housing Code for the Parallel Road lots.

This Summary Table is intended as a guide to the development standards for the construction of a new:

- 1-2 storey dwelling house
- attached development

(Note: attached development means any of the following, if it is situated not more than 900mm from a dwelling house to which it relates and is not exempt development: access ramp, awning, blind or canopy, balcony, deck, patio, pergola, terrace or verandah, basement, cabana, cubby house, fernery, garden shed, gazebo or greenhouse, carport, driveway, garage or hard stand space, pathway or paving, rainwater tank, retaining wall, shed)

• alterations and additions to 1–2 storey dwelling houses and attached development


as complying development on a parallel road lot in Zones R1, R2, R3, R4 and RU5.

Parallel road lot means a lot that has boundaries with 2 parallel roads, not including a lane.



Important Notes

- 1. The area of the lot must not be less than 200m2 and the width of the lot must not be less than 8m measured at the building line. Only 1 dwelling house is permitted on the lot.
- 2. Development standards for excavation, fill, retaining walls and structural supports, drainage, protected tree requirements and protection of adjoining walls associated with dwelling houses are provided under Division 5.
- 3. Development standards for dwelling houses on bush fire prone land and flood control lots are provided under Clauses 3C.5 and 3C.6.
- 4. This Table must be read with all clauses under the Housing Code.
- 5. EPI = Environmental Planning Instrument



Example of a Parallel Road Lot

Disclaimer: The information provided, including summary tables, is intended to be general information only and does not constitute professional advice and should not be relied upon as such. No liability is accepted for reliance on any information that is provided. You should seek independent professional advice and refer to the relevant legislation, including the State Environmental Planning Policy (Exempt and Complying Development Codes) 2008 before taking action, by visiting this link.



Development Standards for a Parallel Road Lot (based on lot area)

							Lot Area	(m2)					
Clause	Built Form Development Standards	200–250	>250- 300	>300- 350	>350- 450	>450- 560	>560- 600	>600- 740	>740- 900	>900- 920	>920- 1000	>1000- 1500	>1500
3C.2	Maximum no. storeys	2											
3C.9	Maximum building height	8.5m	9.5m										
3C.10	Maximum gross floor area of all buildings (Note: When calculating the lot size of a battle-axe lot, the area of the access laneway is excluded.)	78%	75%	235m2	25% + 150m2	290m2	25% + 150m2	335m2	25% + 150m2	380m2	25% + 150m2	400m2	400m2
3C.11 (1)	Primary road setback A dwelling house and any attached development (other than a garage) must be set back from a primary road so that the primary road is at least:	3m from th building lir dwelling h and; 1.5m from articulatio for the dwo house.	ne of the ouse, the n zone	4.5m from the front building line of the dwelling house, and; 3m from the articulation zone for the dwelling house.									<u> </u>



							Lot Area	(m2)						
Clause	Built Form Development Standards		200–250	>250- 300	>300- 350	>350- 450	>450- 560	>560- 600	>600- 740	>740- 900	>900- 920	>920- 1000	>1000- 1500	>1500
3C.11 (9)	Parallel road setbacks for lots	parallel road	Despite any other standard for a setback specified by this clause, a dwelling house and any attached development must have a setback from a boundary with a parallel road of at least 3m. Note. Certain types of attached development may be built within the parallel road setback (see clause 3C.12 (6)).											
	Minimum rear setback for building height of	Building Height												
3C.11 (7)	building height of building heights: (Note: Exceptions to side and rear setbacks apply. See clause 3C.12 (1), (2), (5) and (7) for detail.)	Single storey	3m											
(,,		Two-storey	6m											
3C.11	Minimum setback from	Setback specified in EPI	As specifie	ed by the	EPI									
(10)	classified road	No setback specified in EPI	9m											
3C.11 (11)	Minimum setbacks from pu (Note: public reserve setback dwelling house, cabanas, cub shed, gazebo, fernery, greenh	Зm												



								Lot Area	(m2)					
Clause	Built Form Development Standards		200–250	>250- 300	>300- 350	>350- 450	>450- 560	>560- 600	>600- 740	>740- 900	>900- 920	>920- 1000	>1000- 1500	>1500
3C.12 (5)	Despite 3C.11 (7), a dwelling attached development may lane for up to the following boundary:	y abut a rear	50%											
3C.14	Maximum floor level height of attached side or rear balconies, decks, patios, terraces and verandahs-general where lot area is greater than 300m2 and lot width (measured at the building line) is more than 10m:	Setback from side or rear boundary												
		<3m	Not Permitted	2m										
(1), (2)		3m-6m	Not Permitted	3m										
		>6m	Not Permitted	4m										
3C.14A (1), (2)	Maximum floor level heigh side or rear balconies, deck terraces and verandahs-sn lot area is at least 200m2 a (measured at the building l than 7m:	ks, patios, nall lots, where and lot width	The maxim	um heigh	nt of the l	palcony, d	leck, patio	o, terrace	or veran	dah is 3n	n above g	round le [,]	vel (existi	ng).



	Clause	Built Form Development Standards	Lot Area (m2)											
			200–250	>250- 300	>300- 350	>350- 450	>450- 560	>560- 600	>600- 740	>740- 900	>900- 920	>920- 1000	>1000- 1500	>1500
	3C.14 (3)	Maximum area of attached balconies, decks, patios, terraces and verandahs within 6m of side or rear boundary; and with a floor level >2m above ground	12m2											



Side Setbacks (based on lot width and height of development)

Clause	Built Form Development Standards	Lot Width (at t	he building line)			
Clause			6m-<7m	7m-<10m	10m-<15m	15m or more
	Side setbacks The ground level of a dwelling house and any attached development (other than a garage) must have:	Side A	Om	Om	Om	0.9m
3C.11 (2)	a minimum set back from one side boundary as shown under 'Side A' in the following table in relation to the subject lot, and a minimum setback from the other side boundary as shown under 'Side B' in the table in relation to that lot. The applicant may nominate which side boundary is to be Side A and Side B	Side B	Om	0.9m	0.9m	0.9m
3C.11 (3)	The upper level of a dwelling house and any attached development (other than a garage) must have: a minimum set back from one side boundary as shown under 'Side A' in the following table in relation to the subject lot, and	Side A	1.2m	1.2m	1.2m	1.2m



Clause	Built Form Development Standards	Lot Width (at the building line)								
Clause			6m-<7m	7m-<10m	10m-<15m	15m or more				
	a minimum setback from that side boundary as shown under 'Side B' in the table in relation to that lot, Side A and Side B must be the same sides of the lot at the ground and upper levels.a minimum setback from that side boundary as shown under 'Side B' in the table in relation to that lot, Side A and Side B must be the same sides of the lot at the ground and upper levels.	Side B	Om	0.9m	0.9m	0.9m				

Note:

Building line means the line of the existing or proposed external wall of a building (other than any ancillary development, attached development or detached development) closest to the property boundary adjacent to:

- a. the primary road of the lot, or
- b. in the case of a battle-axe lot, the rear boundary of the dwelling house on the lot in front of the battle-axe lot, or
- c. any other stated boundary of the lot.



Development Standards for a Parallel Road Lot (based on lot width)

Clause	Built Form Development Sta	ndordo		Lot Width (at the bu	ilding line)						
Clause				7m-<10m	10m-<	15m	15m or more				
3C.16, 3C.17, 3C.18	Refer to clause 3C.16 Buil additional amenity require	ding design, 3C.17 Windows ements.	, doors and openings and 3C	.18 Privacy screens for wind	ows and certair	attached d	evelopment for				
3C.19 (1)	Car parking space required on lot (Note: See clause 3C.13 for additional requirements. Please note exclusion of required car parking from calculation of gross floor area)		Not required	1 space required where lot width >8m	1 space requi	red	1 space required				
3C.19	BC.19 Garage and Carport										
(5)	Setback	<4.5m	5.5m								
		4.5m or more	1m or more behind the bui	lding line							
3C.19 (6)	Maximum width of garage doors facing primary, secondary or	Single-storey dwelling	Not applicable, as only rear– loaded garages	3.2m	10m-<11m: 11m-<15m: 3.2m 6m		50% of the façade width to a maximum 7.2m				
	parallel road	Two-storey dwelling	are permitted	3.2m	10m–<11m: 6m 11m–<15m: 6m		50% of the façade width to a maximum 7.2m				



Landscaping Development Standards

			Lot Width (at the building line)									
Clause	Built Form Development Standards	200–300m2 >300m2–450m2		-450m2	>450m2-600m2	>600m2- 900m2	>900m2- 1500m2	>1500m2				
3C.15 (1)	Minimum landscaped area that must be provided on a lot	10%	15%		20%	30%	40%	45%				
Clause	Landscape Development Standards	Lot Width (at the building line)										
Clause		6m-<7n	n		7m-<10m	10m-<15m		15m or more				
3C.15 (3)	Minimum area forward of the building line to be landscaped (Note: Minimum width and length of landscaped area is 1.5m x 1.5m)		25% 15m-18m: 2 >18m: 509									
3C.37 (4)	Trees	-	Front yard: a tree with a mature height of 8m Rear yard: a tree with a mature height of 5m									



	Built Form Development Standards		Lot Width (at the building line)										
Clause		200-300m2	>300m2-450m2	>450m2-600m2	>600m2- 900m2	>900m2- 1500m2	>1500m2						
3C.36 (1)	Pruning and removal of trees	any requirem other vegetat (a) the tree is (b) the tree or (c) the tree or	ent under this Polic ion on the lot if: not listed on a reg vegetation will be vegetation has a h ment that is the ere consent, or	ficate for complying cy for a permit or de ister of significant within 3m of any b neight that is less th ection of a dwelling	evelopment co trees kept by uilding that ha nan:	onsent to remove the council, and; as an area of mo	or prune a tree or						