

Summary of Greenfield Housing Code Development Standards (Standard Lot)

This document includes a summary of the development standards of Greenfield Housing Code for the Standard lots.

This Summary Table is intended as a guide to the development standards for the construction of a new:

- 1–2 storey dwelling house
- attached development

(Note: attached development means any of the following, if it is situated not more than 900mm from a dwelling house to which it relates and is not exempt development: access ramp, awning, blind or canopy, balcony, deck, patio, pergola, terrace or verandah, basement, cabana, cubby house, fernery, garden shed, gazebo or greenhouse, carport, driveway, garage or hard stand space, pathway or paving, rainwater tank, retaining wall, shed)

• alterations and additions to 1–2 storey dwelling houses and attached development


as complying development on a parallel road lot in Zones R1, R2, R3, R4 and RU5.

Standard lot means a lot that is not a battle-axe lot, a corner lot or a parallel road lot.



Important Notes

- 1. The area of the lot must not be less than 200m2 and the width of the lot must not be less than 8m measured at the building line. Only 1 dwelling house is permitted on the lot.
- 2. Development standards for excavation, fill, retaining walls and structural supports, drainage, protected tree requirements and protection of adjoining walls associated with dwelling houses are provided under Division 5.
- 3. Development standards for dwelling houses on bush fire prone land and flood control lots are provided under Clauses 3C.5 and 3C.6.
- 4. This Table must be read with all clauses under the Housing Code.
- 5. EPI = Environmental Planning Instrument



Example of a Standard Lot

Disclaimer: The information provided, including summary tables, is intended to be general information only and does not constitute professional advice and should not be relied upon as such. No liability is accepted for reliance on any information that is provided. You should seek independent professional advice and refer to the relevant legislation, including the State Environmental Planning Policy (Exempt and Complying Development Codes) 2008 before taking action, by visiting this link.



Development Standards for a Standard Lot (based on lot area)

								Lot Area	(m2)					
Clause	Built Form Development Standards		200-250	>250- 300	>300- 350	>350- 450	>450- 560	>560- 600	>600- 740	>740- 900	>900- 920	>920- 1000	>1000- 1500	>1500
3C.2	Maximum no. storeys		2											
3C.9	Maximum building height		8.5m	8.5m										
3C.10	Maximum gross floor area (Note: When calculating the lo battle–axe lot, the area of the is excluded.)	78%	75%	235m2	25% + 150m2	290m2	25% + 150m2	335m2	25% + 150m2	380m2	25% + 150m2	400m2	400m2	
3C.11 (1)	development (other than a	dwelling house, and; and; opment (other than a garage) must at back from a primary road so that articulation zone.			4.5m from the front building line of the dwelling house, and; 3m from the articulation zone for the dwelling house.									
3C.11	building height of	Building Height												
(7)		Single storey	3m											



	Built Form Development Standards			Lot Area (m2)											
Clause			200-250	>250- 300	>300- 350	>350- 450	>450- 560	>560- 600	>600- 740	>740- 900	>900- 920	>920- 1000	>1000- 1500	>1500	
	(Note: Exceptions to side and rear setbacks apply. See clause 3C.12 (1), (2), (5) and (7) for detail.)	Two-storey	6m												
3C.11 (10)	Minimum setback from	Setback specified in EPI	As specific	ed by the	EPI										
	classified road	No setback specified in EPI	9m												
3C.11 (11)	Minimum setbacks from po (Note: public reserve setback dwelling house, cabanas, cub shed, gazebo, fernery, greenh	applies to a by house, garden	3m												
3C.12 (5)	Despite 3C.11 (7), a dwellin attached development ma lane for up to the following boundary:	y abut a rear	50%	50%											
3C.14 (1), (2)	Maximum floor level height of attached side or rear balconies, decks,	Setback from side or rear boundary													



		Lot Area (m2)												
Clause	Built Form Development Standards		200–250	>250- 300	>300- 350	>350- 450	>450- 560	>560- 600	>600- 740	>740- 900	>900- 920	>920- 1000	>1000- 1500	>1500
	patios, terraces and verandahs where lot area is greater than 300m2 and lot width (measured at the building line) is more than 10m:	<3m	Not Permitted	2m										
		3m-6m	Not Permitted	3m										
		>6m	Not Permitted	4m										
3C.14A (1), (2)	Maximum floor level height of attached side or rear balconies, decks, patios, terraces and verandahs-small lots, where lot area is at least 200m2 and lot width (measured at the building line) is more than 7m: The maximum height of the balcony, deck, particles and the building line is more than 7m:					deck, patio	o, terrace	or veran	dah is 3r	m above ຊ	ground le	vel (existi	ng).	
3C.14 (3)	Maximum area of attached decks, patios, terraces and within 6m of side or rear bo with a floor level >2m abov	12m2												



Side Setbacks (based on lot width and height of development)

Clause	Built Form Development Standards	Lot Width (at the building line)									
Clause	Built Form Development Standards		6m-<7m	7m-<10m	10m-<15m	15m or more					
	Side setbacks The ground level of a dwelling house and any attached development (other than a garage) must have:	Side A	Om	0m	Om	0.9m					
3C.11 (2)	a minimum set back from one side boundary as shown under 'Side A' in the following table in relation to the subject lot, and a minimum setback from the other side boundary as shown under 'Side B' in the table in relation to that lot. The applicant may nominate which side boundary is to be Side A and Side B	Side B	Om	0.9m	0.9m	0.9m					
3C.11 (3)	The upper level of a dwelling house and any attached development (other than a garage) must have: a minimum set back from one side boundary as shown under 'Side A' in the following table in relation to the subject lot, and	Side A	1.2m	1.2m	1.2m	1.2m					



	Clause	Built Form Development Standards	Lot Width (at the building line)								
		Built Form Development Standards		6m-<7m	7m-<10m	10m-<15m	15m or more				
		a minimum setback from that side boundary as shown under 'Side B' in the table in relation to that lot, Side A and Side B must be the same sides of the lot at the ground and upper levels.a minimum setback from that side boundary as shown under 'Side B' in the table in relation to that lot, Side A and Side B must be the same sides of the lot at the ground and upper levels.	Side B	Om	0.9m	0.9m	0.9m				

Note:

Building line means the line of the existing or proposed external wall of a building (other than any ancillary development, attached development or detached development) closest to the property boundary adjacent to:

- a. the primary road of the lot, or
- b. in the case of a battle-axe lot, the rear boundary of the dwelling house on the lot in front of the battle-axe lot, or
- c. any other stated boundary of the lot.



Development Standards for a Parallel Road Lot (based on lot width)

Clause	Built Form Development Sta	n dordo		Lot Width (at the bui	lding line)					
Clause	Built Form Development Sta	nuarus	6m-<7m	7m-<10m	10m-<	15m	15m or more			
3C.16, 3C.17, 3C.18	Refer to clause 3C.16 Buil additional amenity require	ding design, 3C.17 Windows, ements.	doors and openings and 3C	.18 Privacy screens for windo	ows and certair	n attached d	evelopment for			
3C.19 (1)	Car parking space required on lot (Note: See clause 3C.13 for additional requirements. Please note exclusion of required car parking from calculation of gross floor area)		Not required	1 space required where lot width >8m	1 space required		1 space required			
3C.19	Minimum Primary Road Garage and Carport	Dwelling primary road setback								
(5)	Setback	<4.5m	5.5m							
		4.5m or more	1m or more behind the buil	ding line						
3C.19 (6)	Maximum width of garage doors facing primary, secondary or	Single-storey dwelling	Not applicable, as only rear–loaded garages	3.2m	10m-<11m: 3.2m	11m-<15m: 6m	50% of the façade width to a maximum 7.2m			
	parallel road	Two-storey dwelling	are permitted	3.2m	10m-<11m: 6m 11m-<15m: 6m		50% of the façade width to a maximum 7.2m			



Landscaping Development Standards

			Lot Width (at the building line)									
Clause	Built Form Development Standards	200-300m2 >300m2-450		-450m2	>450m2-600m2	>600m2- 900m2		>900m2- 1500m2	>1500m2			
3C.15 (1)	Minimum landscaped area that must be provided on a lot	10%	15%		20%	30%		40%	45%			
01	Landsons Davelanment Standards	Lot Width (at the building line)										
Clause	Landscape Development Standards	6m-<7m			7m-<10m		10m-	-<15m	15m or more			
3C.15 (3)	Minimum area forward of the building line to be landscaped (Note: Minimum width and length of landscaped area is 1.5m x 1.5m)	25% 15m-18m: 25% >18m: 50%										
3C.37 (4)	Trees		Front yard: a tree with a mature height of 8m Rear yard: a tree with a mature height of 5m									



	Built Form Development Standards	Lot Width (at the building line)										
Clause		200-300m2	>300m2-450m2	>450m2-600m2	>600m2- 900m2	>900m2- 1500m2	>1500m2					
3C.36 (1)	Pruning and removal of trees	any requirem other vegeta (a) the tree is (b) the tree of (c) the tree of	ent under this Police tion on the lot if: not listed on a regreen regetation will be regetation has a had ment that is the ereconsent, or	cy for a permit or de ister of significant within 3m of any b neight that is less th	trees kept by uilding that ha	nsent to remove the council, and; as an area of mo						